

View Online at <https://aerobasegroup.com/nsn/5340-01-342-7387>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.995 inches

**Second Leg Length:**

2.005 inches

**Reinforcement Method (non-core):**

Gusset first leg

**Second Leg Width:**

5.500 inches

**First Leg Hole Diameter:**

Between 0.332 inches and 0.338 inches

**Second Leg Hole Diameter:**

Between 0.310 inches and 0.360 inches

**Second Leg Distance Between Hole Centers Along Width:**

4.500 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

5.500 inches

**First Leg Distance Between Hole Centers Along Length:**

1.875 inches

**First Leg Distance From Edge To Hole Center Along Width:**

2.500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.480 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Cut out

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Cutout Length:**

1.880 inches

**Second Leg Cutout Width:**

3.620 inches

**Material:**

Aluminum alloy 5052 or aluminum alloy 5086

**Material Specification:**

Qq-a-250/8 federal specification 1st material response or qq-a-250/7 federal specification 2nd material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.