

View Online at <https://aerobasegroup.com/nsn/5340-01-342-7387>

Mounting Hole Type:

Plain

First Leg Length:

0.995 inches

Second Leg Length:

2.005 inches

Reinforcement Method (non-core):

Gusset first leg

Second Leg Width:

5.500 inches

First Leg Hole Diameter:

Between 0.332 inches and 0.338 inches

Second Leg Hole Diameter:

Between 0.310 inches and 0.360 inches

Second Leg Distance Between Hole Centers Along Width:

4.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

5.500 inches

First Leg Distance Between Hole Centers Along Length:

1.875 inches

First Leg Distance From Edge To Hole Center Along Width:

2.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.480 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Cut out

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Cutout Length:

1.880 inches

Second Leg Cutout Width:

3.620 inches

Material:

Aluminum alloy 5052 or aluminum alloy 5086

Material Specification:

Qq-a-250/8 federal specification 1st material response or qq-a-250/7 federal specification 2nd material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.