

View Online at <https://aerobasegroup.com/nsn/5340-01-343-1184>

**Thread Class:**

3a rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

0.800 inches rod connection

**Shank Length:**

3.200 inches

**Hole Diameter:**

Between 0.625 inches and 0.626 inches

**Shank Diameter:**

Between 0.6225 inches and 0.6235 inches

**Overall Height:**

1.250 inches

**Overall Width:**

Between 1.250 inches and 1.260 inches

**End Radius:**

0.625 inches

**Fork Span Width:**

Between 0.670 inches and 0.680 inches

**Securing Pin Hole Diameter:**

Between 0.076 inches and 0.082 inches

**Distance From Center Of Securing Pin Hole To Rod End:**

0.170 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

5.150 inches

**Fork Arm Thickness:**

Between 0.280 inches and 0.290 inches

**Fork Depth:**

1.250 inches

**Thread Size:**

0.500 inches rod connection

**Special Features:**

Finish gray

**Material:**

Steel comp xm-12

**Material Specification:**

Ams 5659 assn standard single material response

**Surface Treatment:**

Paint

**Surface Treatment Specification:**

Mil-p-23377 military specification single treatment response

**Style Designator:**

Clevis

**Thread Series Designator:**

Unjf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A264a0

**Mil-std (military Standard):**

Mil-p-23377 spec.