NSN 5340-01-343-4254

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-343-4254

| Maunting Hala Tuna |
|------------------------------------------------------------|
| Mounting Hole Type: |
| Threaded |
| First Leg Length: |
| 0.380 inches |
| Second Leg Length: |
| 1.020 inches |
| Second Leg Width: |
| 3.940 inches |
| Second Leg Hole Diameter: |
| 0.086 inches |
| Second Leg Distance Between Hole Centers Along Width: |
| 3.543 inches |
| Second Leg Distance From Edge To Hole Center Along Width: |
| 0.200 inches |
| Second Leg Distance From Edge To Hole Center Along Length: |
| 0.188 inches |
| First Leg Thickness: |
| 0.400 inches |
| Second Leg Thickness: |
| 0.200 inches |
| First Leg Width: |
| 3.940 inches |
| First Leg Style: |
| Square |
| First Leg Hole Arrangement Style: |
| No hole |
| Second Leg Style: |
| Cut out |
| Second Leg Hole Arrangement Style: |
| Two holes |
| Second Leg Relationship To First Leg: |
| Not identical |
| First Leg Angle: |
| 90.0 degrees |
| Second Leg Cutout Length: |
| 0.430 inches |
| Second Leg Cutout Width: |
| 3.293 inches |
| Material: |
| |
| Aluminum alloy 6061 |

Qq-a-250/11 t651 federal specification single material response

NSN 5340-01-343-4254

Angle Bracket - Page 2 of 2

Mil-std (military Standard):

Mil-c-5541 spec.



| Surface Treatment: |
|-------------------------------------------------------------------|
| Chromate |
| Surface Treatment Specification: |
| Mil-c-5541, cl 3 military specification single treatment response |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A042a0 |