NSN 5340-01-344-2531

Access Cover - Page 1 of 2

Surface Treatment: Paint polyurethane



View Online at https://aerobasegroup.com/nsn/5340-01-344-2531

Cross Sectional Shape:
Flat
Hole Diameter:
Between 0.250 inches and 0.310 inches
Width:
5.620 inches
Edge Shape:
Rectangle, multi holes
Length:
5.620 inches
Corner Radius:
0.120 inches
Hole Quantity Along Length:
4
Hole Quantity Along Width:
4
Distance Between Holes Along Length:
0.850 inches and 3.000 inches
Distance Between Holes Along Width:
0.850 inches and 3.000 inches
Distance Between Hole Centerline And First Hole Along Length:
0.850 inches
Distance Between Hole Centerline And First Hole Along Width:
0.850 inches
Distance From First Hole Centerline To End Along Length:
1.310 inches
Distance From First Hole Centerline To End Along Width:
1.310 inches
Body Thickness:
0.090 inches
Securing Device Type:
Special
Mounting Opening Shape Style:
Unthreaded hole
Special Features:
Color green 383
Material:
Aluminum alloy 5052 or aluminum alloy 5086
Material Specification:
Qq-a-250/8 federal specification 1st material response or astm b209 assn standard 2nd material response or qq-a-250/7 federal specification
2nd material response

NSN 5340-01-344-2531

Access Cover - Page 2 of 2



Surface Treatment Specification:

Mil-c-46168 military specification single treatment	response or mil-c-53039 military	specification single treatment response
---	----------------------------------	---

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531c0

Mil-std (military Standard):

Mil-c-46168 spec.