

View Online at <https://aerobasegroup.com/nsn/5340-01-344-5974>

Mounting Hole Type:

Countersunk and plain

First Leg Length:

1.250 inches

Second Leg Length:

1.250 inches

Second Leg Width:

29.100 inches

First Leg Hole Diameter:

0.272 inches

Second Leg Hole Diameter:

0.288 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

9.062 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

11.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

4.390 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.190 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

29.100 inches

First Leg Distance Between Hole Centers Along Width:

28.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.550 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Three holes

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

4 rivets, ms20426ad4-12; 1 shim, 20.050 in. Long, 1.250 in. Wide; 0.090 in. Thk

Material:

Aluminum alloy 6063

Material Specification:

Qq-a-200/9 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-f-14072, e513 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-f-14072 spec.