NSN 5340-01-345-6422

Strap Hinge Leaf - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-345-6422

Material Thickness:
0.125 inches
Mounting Hole Diameter:
Between 0.193 inches and 0.200 inches
Mounting Hole Quantity:
2
Body Width:
0.450 inches
Performance Type:
Not rated
Reversible Feature:
Not included
Knuckle Quantity:
2
Pin Center To Body Edge Distance:
1.188 inches
Knuckle Type:
Friction
Material And Location:
Steel
Steel
Steel Surface Treatment And Location:
Steel Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 2
Steel Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 2 Special Features:
Steel Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 2 Special Features: 0.128 - 0.133 in diameter pin hole; 1000 lb min load, mates w/-3, -4, -5, -6, -7 latch assembly
Steel Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 2 Special Features: 0.128 - 0.133 in diameter pin hole; 1000 lb min load, mates w/-3, -4, -5, -6, -7 latch assembly Style Designator:
Streel Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 2 Special Features: 0.128 - 0.133 in diameter pin hole; 1000 lb min load, mates w/-3, -4, -5, -6, -7 latch assembly Style Designator: Strap
Streel Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 2 Special Features: 0.128 - 0.133 in diameter pin hole; 1000 lb min load, mates w/-3, -4, -5, -6, -7 latch assembly Style Designator: Strap Shelf Life:
Strace Treatment And Location: Cadmium, qq-p-416, type 2, class 2 Special Features: 0.128 - 0.133 in diameter pin hole; 1000 lb min load, mates w/-3, -4, -5, -6, -7 latch assembly Style Designator: Strap Shelf Life: N/a
Strace Treatment And Location: Cadmium, qq-p-416, type 2, class 2 Special Features: 0.128 - 0.133 in diameter pin hole; 1000 lb min load, mates w/-3, -4, -5, -6, -7 latch assembly Style Designator: Strap Shelf Life: N/a
Streel Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 2 Special Features: 0.128 - 0.133 in diameter pin hole; 1000 lb min load, mates w/-3, -4, -5, -6, -7 latch assembly Style Designator: Strap Shelf Life: N/a Unit Of Measure:
Streel Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 2 Special Features: 0.128 - 0.133 in diameter pin hole; 1000 lb min load, mates w/-3, -4, -5, -6, -7 latch assembly Style Designator: Strap Shelf Life: N/a Unit Of Measure: Demilitarization:
Steel Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 2 Special Features: 0.128 - 0.133 in diameter pin hole; 1000 lb min load, mates w/-3, -4, -5, -6, -7 latch assembly Style Designator: Strap Shelf Life: N/a Unit Of Measure: Demilitarization: No
Steel Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 2 Special Features: 0.128 - 0.133 in diameter pin hole; 1000 lb min load, mates w/-3, -4, -5, -6, -7 latch assembly Style Designator: Strap Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: