

View Online at <https://aerobasegroup.com/nsn/5340-01-348-3218>

Mounting Hole Type:

Plain

First Leg Length:

27.0 millimeters

Second Leg Length:

35.0 millimeters

Second Leg Width:

65.0 millimeters

Second Leg End Width:

15.0 millimeters

First Leg Hole Diameter:

Between 11.17 millimeters and 11.38 millimeters

Second Leg Hole Diameter:

Between 3.53 millimeters and 3.77 millimeters

Second Leg Distance Between Upper Hole Centers Along Width:

53.0 millimeters

Second Leg Distance Between Hole Centers Along Length:

20.0 major inches

Second Leg Distance Between First And Second Hole Centers Along Width:

26.5 millimeters

Second Leg Distance From Edge To Hole Center Along Width:

6.0 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

5.0 millimeters

First Leg Thickness:

1.57 millimeters

Second Leg Thickness:

1.57 millimeters

First Leg Width:

65.0 millimeters

First Leg End Width:

49.0 millimeters

First Leg Distance Between Hole Centers Along Width:

25.0 millimeters

First Leg Distance From Edge To Hole Center Along Width:

20.0 millimeters

First Leg Distance From Edge To Hole Center Along Length:

11.5 millimeters

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 h32 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 cl 3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.