NSN 5340-01-348-3218

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-348-3218

Mounting Hole Type:
Plain
First Leg Length:
27.0 millimeters
Second Leg Length:
35.0 millimeters
Second Leg Width:
65.0 millimeters
Second Leg End Width:
15.0 millimeters
First Leg Hole Diameter:
Between 11.17 millimeters and 11.38 millimeters
Second Leg Hole Diameter:
Between 3.53 millimeters and 3.77 millimeters
Second Leg Distance Between Upper Hole Centers Along Width:
53.0 millimeters
Second Leg Distance Between Hole Centers Along Length:
20.0 major inches
Second Leg Distance Between First And Second Hole Centers Along Width:
26.5 millimeters
Second Leg Distance From Edge To Hole Center Along Width:
6.0 millimeters
Second Leg Distance From Edge To Hole Center Along Length:
5.0 millimeters
First Leg Thickness:
1.57 millimeters
Second Leg Thickness:
1.57 millimeters
First Leg Width:
65.0 millimeters
First Leg End Width:
49.0 millimeters
First Leg Distance Between Hole Centers Along Width:
25.0 millimeters
First Leg Distance From Edge To Hole Center Along Width:
20.0 millimeters
First Leg Distance From Edge To Hole Center Along Length:
11.5 millimeters
First Leg Style:
Chamfered ends
First Leg Hole Arrangement Style:
Two holes

NSN 5340-01-348-3218

Angle Bracket - Page 2 of 2



Second Leg Style:
Chamfered ends
Second Leg Hole Arrangement Style:
Three holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
First Leg Chamfer Angle:
45.0 degrees
Second Leg Chamfer Angle:
45.0 degrees
Material:
Aluminum alloy 5052
Material Specification:
Qq-a-250/8 h32 federal specification single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541 cl 3 military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-c-5541 spec.