

View Online at <https://aerobasegroup.com/nsn/5340-01-350-2264>

Mounting Hole Type:

Plain

First Leg Length:

Between 1.310 inches and 1.330 inches

Second Leg Length:

Between 1.360 inches and 1.380 inches

Second Leg Width:

1.590 inches

Second Leg Corner Radius:

Between 0.050 inches and 0.080 inches

First Leg Hole Diameter:

Between 0.163 inches and 0.172 inches

Second Leg Hole Diameter:

Between 0.163 inches and 0.172 inches

Second Leg Distance Between Hole Centers Along Width:

1.290 inches

Second Leg Distance Between Hole Centers Along Length:

0.580 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.140 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.180 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

Between 0.840 inches and 0.860 inches

First Leg Corner Radius:

Between 0.050 inches and 0.080 inches

First Leg Distance From Edge To Hole Center Along Width:

0.230 inches

First Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 0.04 radians and 0.06 radians

Special Features:

Plastic polychlorofluoroethylene

Material:

Aluminum alloy 2024 or aluminum alloy 6061 or aluminum alloy 7075

Material Specification:

Qq-a-250/4 federal specification 1st material response or qq-a-250/11 federal specification 2nd material response or qq-a-250/12 federal specification 3rd material response

Surface Treatment Specification:

Mil-c-22750 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-22750 spec.