

View Online at <https://aerobasegroup.com/nsn/5340-01-350-2264>

**Mounting Hole Type:**

Plain

**First Leg Length:**

Between 1.310 inches and 1.330 inches

**Second Leg Length:**

Between 1.360 inches and 1.380 inches

**Second Leg Width:**

1.590 inches

**Second Leg Corner Radius:**

Between 0.050 inches and 0.080 inches

**First Leg Hole Diameter:**

Between 0.163 inches and 0.172 inches

**Second Leg Hole Diameter:**

Between 0.163 inches and 0.172 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.290 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.580 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.140 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.180 inches

**First Leg Thickness:**

0.040 inches

**Second Leg Thickness:**

0.040 inches

**First Leg Width:**

Between 0.840 inches and 0.860 inches

**First Leg Corner Radius:**

Between 0.050 inches and 0.080 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.230 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.310 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

Between 0.04 radians and 0.06 radians

**Special Features:**

Plastic polychlorofluoroethylene

**Material:**

Aluminum alloy 2024 or aluminum alloy 6061 or aluminum alloy 7075

**Material Specification:**

Qq-a-250/4 federal specification 1st material response or qq-a-250/11 federal specification 2nd material response or qq-a-250/12 federal specification 3rd material response

**Surface Treatment Specification:**

Mil-c-22750 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-22750 spec.