

View Online at <https://aerobasegroup.com/nsn/5340-01-350-6892>

Mounting Hole Type:

Plain

First Leg Length:

1.060 inches

Second Leg Length:

2.711 inches

Reinforcement Method (non-core):

Rib stiffener first leg

Second Leg Width:

4.809 inches

First Leg Hole Diameter:

Between 0.193 inches and 0.199 inches

Second Leg Hole Diameter:

Between 0.260 inches and 0.267 inches

Second Leg Distance Between Upper Hole Centers Along Width:

1.174 inches

Second Leg Distance Between Hole Centers Along Length:

1.706 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.169 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.388 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.440 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

4.809 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

1.660 inches

First Leg Distance From Edge To Hole Center Along Width:

0.380 inches

First Leg Distance From Edge To Hole Center Along Length:

0.450 inches

Second Leg End Radius:

0.440 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

1 of 3 holes in 2nd leg 0.237 in. Min, 0.243 in. Maximum dia

Material:

Titanium alloy

Material Specification:

Mil-t-81556 military specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-t-81556 spec.