

View Online at <https://aerobasegroup.com/nsn/5340-01-351-1895>

Mounting Hole Type:

Plain

First Leg Length:

1.000 inches

Second Leg Length:

2.120 inches

Second Leg Width:

7.000 inches

First Leg Hole Diameter:

Between 0.328 inches and 0.331 inches

Second Leg Hole Diameter:

Between 0.328 inches and 0.331 inches

Second Leg Distance Between Hole Centers Along Width:

6.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.315 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

7.000 inches

First Leg Distance Between Hole Centers Along Width:

5.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Length:

0.380 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Cut out

Second Leg Hole Arrangement Style:

Two holes

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.090 radians

Second Leg Cutout Length:

1.000 inches

Second Leg Cutout Width:

4.000 inches

Special Features:

Item includes r clinch nuts pressed into mtg holes, 6-32 unc thread

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, temp h32 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.