

View Online at <https://aerobasegroup.com/nsn/5340-01-351-3292>

Mounting Hole Type:

Plain

First Leg Length:

0.940 inches

Second Leg Length:

1.000 inches

Reinforcement Method (non-core):

Turned edge second leg

Second Leg Width:

3.750 inches

First Leg Hole Diameter:

Between 0.187 inches and 0.193 inches

Second Leg Hole Diameter:

0.500 inches

Second Leg Distance Between Hole Centers Along Width:

2.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.435 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

4.250 inches

First Leg End Width:

3.990 inches

First Leg Distance Between Hole Centers Along Width:

3.750 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.750 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

1.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.375 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Cut out

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Cutout Length:

0.960 inches

Second Leg Cutout Width:

1.620 inches

First Leg Chamfer Angle:

45.0 degrees

Special Features:

2nd leg turned edge 0.560 in. Lg, 1.000 in. W; has cutout 0.415 in. W, 0.300 in. Lg; one hole in 1st leg 0.500 in. Dia

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t4 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, cl 2, color black military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.