Angle Bracket - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5340-01-351-3292



Mounting Hole Type:
Plain
First Leg Length:
0.940 inches
Second Leg Length:
1.000 inches
Reinforcement Method (non-core):
Turned edge second leg
Second Leg Width:
3.750 inches
First Leg Hole Diameter:
Between 0.187 inches and 0.193 inches
Second Leg Hole Diameter:
0.500 inches
Second Leg Distance Between Hole Centers Along Width:
2.750 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.500 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.435 inches
First Leg Thickness:
0.040 inches
Second Leg Thickness:
0.040 inches
First Leg Width:
4.250 inches
First Leg End Width:
3.990 inches
First Leg Distance Between Hole Centers Along Width:
3.750 inches
First Leg Distance Between First And Second Hole Centers Along Width:
0.750 inches
First Leg Distance Between Second And Third Hole Centers Along Width:
1.500 inches
First Leg Distance From Edge To Hole Center Along Width:
0.250 inches
First Leg Distance From Edge To Hole Center Along Length:
0.375 inches
First Leg Style:
Chamfered ends
First Leg Hole Arrangement Style:
Four holes

NSN 5340-01-351-3292

Angle Bracket - Page 2 of 2

--



Second Leg Style: Cut out Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical **First Leg Angle:** 90.0 degrees Second Leg Cutout Length: 0.960 inches Second Leg Cutout Width: 1.620 inches First Leg Chamfer Angle: 45.0 degrees **Special Features:** 2nd leg turned edge 0.560 in. Lg, 1.000 in. W; has cutout 0.415 in. W, 0.300 in. Lg; one hole in 1st leg 0.500 in. Dia Material: Aluminum alloy 6061 **Material Specification:** Qq-a-250/11, t4 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 2, cl 2, color black military specification single treatment response **Style Designator:** Angle Shelf Life: N/a Unit Of Measure: **Demilitarization:** Yes - demil/mli Fiig: A042a0 Mil-std (military Standard): Mil-a-8625 spec.