

View Online at <https://aerobasegroup.com/nsn/5340-01-351-9449>

Mounting Hole Type:

Plain

First Leg Length:

1.200 inches

Second Leg Length:

1.650 inches

Second Leg Width:

2.070 inches

Second Leg End Width:

0.480 inches

First Leg Hole Diameter:

Between 0.137 inches and 0.143 inches

Second Leg Hole Diameter:

Between 0.165 inches and 0.171 inches

Second Leg Distance Between Upper Hole Centers Along Width:

0.750 inches

Second Leg Distance Between Hole Centers Along Length:

1.000 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.330 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

2.070 inches

First Leg Distance Between Hole Centers Along Width:

1.718 inches

First Leg Distance From Edge To Hole Center Along Width:

0.176 inches

First Leg Distance From Edge To Hole Center Along Length:

0.530 inches

First Leg Style:

Cut out

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

120.0 degrees

First Leg Cutout Length:

1.020 inches

First Leg Cutout Width:

1.470 inches

Special Features:

1st leg 2 corners chamfered 0.120 in. By 0.120 in.

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t4 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, cl 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.