

View Online at <https://aerobasegroup.com/nsn/5340-01-351-9449>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.200 inches

**Second Leg Length:**

1.650 inches

**Second Leg Width:**

2.070 inches

**Second Leg End Width:**

0.480 inches

**First Leg Hole Diameter:**

Between 0.137 inches and 0.143 inches

**Second Leg Hole Diameter:**

Between 0.165 inches and 0.171 inches

**Second Leg Distance Between Upper Hole Centers Along Width:**

0.750 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.000 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

0.330 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

2.070 inches

**First Leg Distance Between Hole Centers Along Width:**

1.718 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.176 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.530 inches

**First Leg Style:**

Cut out

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square and tapered

**Second Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

120.0 degrees

**First Leg Cutout Length:**

1.020 inches

**First Leg Cutout Width:**

1.470 inches

**Special Features:**

1st leg 2 corners chamfered 0.120 in. By 0.120 in.

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11, t4 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2, cl 2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.