

View Online at <https://aerobasegroup.com/nsn/5340-01-352-2652>

Mounting Hole Type:

Threaded

First Leg Length:

0.500 inches

Second Leg Length:

0.750 inches

Second Leg Width:

5.500 inches

Second Leg Corner Radius:

0.250 inches

First Leg Hole Diameter:

0.138 inches

Second Leg Hole Diameter:

0.138 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.500 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

2.250 inches

Second Leg Distance Between Third And Fourth Hole Centers Along Width:

1.500 inches

First Leg Thickness:

0.156 inches

Second Leg Thickness:

0.156 inches

First Leg Width:

5.500 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.218 inches

First Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Distance Between First And Second Hole Centers Along Length:

2.000 inches

First Leg Distance Between Second And Third Hole Centers Along Length:

2.000 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Corner radius

First Leg Angle:

74.0 degrees

Special Features:

Furnished with helicoil inserts

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-200/8, t6 federal specification single material response

Surface Treatment:

Anodize and paint

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response and 595 no. 37078 federal standard 2nd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.