

View Online at <https://aerobasegroup.com/nsn/5340-01-352-6806>

Mounting Hole Type:

Plain

First Leg Length:

Between 0.550 inches and 0.630 inches

Second Leg Length:

Between 0.880 inches and 0.900 inches

End Application:

Pacer dawn

Second Leg Width:

Between 1.610 inches and 1.680 inches

Second Leg End Width:

Between 1.610 inches and 1.630 inches

First Leg Hole Diameter:

Between 0.204 inches and 0.212 inches

Second Leg Hole Diameter:

Between 0.101 inches and 0.103 inches

Second Leg Distance Between Hole Centers Along Width:

1.455 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.100 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.430 inches and 0.450 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

Between 1.660 inches and 1.680 inches

First Leg End Width:

Between 1.062 inches and 1.082 inches

First Leg Distance Between Hole Centers Along Width:

0.892 inches

First Leg Distance From Edge To Hole Center Along Width:

0.390 inches

First Leg Distance From Edge To Hole Center Along Length:

0.210 inches

First Leg Style:

Square and tapered

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Material:

Stainless steel

Material Specification:

Ms 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0