

View Online at <https://aerobasegroup.com/nsn/5340-01-352-6808>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.880 inches

**Second Leg Length:**

2.880 inches

**Second Leg Width:**

2.750 inches

**Second Leg End Width:**

2.250 inches

**First Leg Slot Length:**

0.375 inches

**First Leg Slot Width:**

0.219 inches

**Second Leg Hole Diameter:**

Between 0.204 inches and 0.211 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.375 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.250 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.685 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.763 inches

**First Leg Thickness:**

0.062 inches

**Second Leg Thickness:**

0.062 inches

**First Leg Width:**

2.750 inches

**First Leg Distance Between Hole Centers Along Width:**

1.875 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.440 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.440 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Chamfer Angle:**

45.0 degrees

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8 h32 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541 cl 1a military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.