# NSN 5340-01-352-8160

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-352-8160

Mounting Hole Type:
Plain
First Leg Length:
Between 0.630 inches and 0.750 inches
Second Leg Length:
Between 2.820 inches and 2.940 inches
Second Leg Width:
Between 0.940 inches and 1.060 inches
Second Leg Distance Between Hole Centers Along Length:
1.000 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.470 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.375 inches
Second Leg Slot Length:
Between 0.590 inches and 0.650 inches
Second Leg Slot Width:
Between 0.375 inches and 0.395 inches
First Leg Thickness:
0.1196 inches
Second Leg Thickness:
0.1196 inches
Center Section Height:
Between 1.280 inches and 1.400 inches
Center Section Width:
Between 0.940 inches and 1.060 inches
Center Section Thickness:
0.1196 inches
First Leg Width:
Between 0.940 inches and 1.060 inches
First Leg End Width:
Between 0.440 inches and 0.560 inches
First Leg Hole Arrangement Style:
No hole
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
2 slots
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees

## NSN 5340-01-352-8160

Double Angle Bracket - Page 2 of 2



Material:

Steel comp 1009

## Material Specification:

Stm a569 assn standard single material response or astm a366 assn standard single material response

### Surface Treatment:

Cadmium and chromate or zinc

## Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification 1st treatment response or astm b633 type 1 cl 2 assn standard 2nd treatment response

## Style Designator:

Adjacent angles

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A042a0