

View Online at <https://aerobasegroup.com/nsn/5340-01-353-7228>

First Leg Length:

Between 2.160 inches and 2.220 inches

Second Leg Length:

Between 2.720 inches and 2.780 inches

End Application:

Pacer dawn

Second Leg Width:

Between 1.850 inches and 1.910 inches

First Leg Hole Diameter:

Between 1.090 inches and 1.150 inches

Second Leg Slot Length:

Between 0.860 inches and 0.900 inches

Second Leg Slot Width:

Between 0.210 inches and 0.230 inches

First Leg Thickness:

0.062 inches

Second Leg Thickness:

0.062 inches

First Leg Width:

Between 1.850 inches and 1.910 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.920 inches and 0.960 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 1.220 inches and 1.280 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

0.120 radians

Second Leg Chamfer Angle:

0.120 radians

Material:

Steel comp 304 or steel comp 316 or steel comp 321 or steel comp 347

Material Specification:

Qq-s-766 federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0