

View Online at <https://aerobasegroup.com/nsn/5340-01-353-7228>

**First Leg Length:**

Between 2.160 inches and 2.220 inches

**Second Leg Length:**

Between 2.720 inches and 2.780 inches

**End Application:**

Pacer dawn

**Second Leg Width:**

Between 1.850 inches and 1.910 inches

**First Leg Hole Diameter:**

Between 1.090 inches and 1.150 inches

**Second Leg Slot Length:**

Between 0.860 inches and 0.900 inches

**Second Leg Slot Width:**

Between 0.210 inches and 0.230 inches

**First Leg Thickness:**

0.062 inches

**Second Leg Thickness:**

0.062 inches

**First Leg Width:**

Between 1.850 inches and 1.910 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.920 inches and 0.960 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 1.220 inches and 1.280 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**First Leg Chamfer Angle:**

0.120 radians

**Second Leg Chamfer Angle:**

0.120 radians

**Material:**

Steel comp 304 or steel comp 316 or steel comp 321 or steel comp 347

**Material Specification:**

Qq-s-766 federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0