

View Online at <https://aerobasegroup.com/nsn/5340-01-353-9008>

Mounting Hole Type:

Threaded and plain

First Leg Length:

2.780 inches

Second Leg Length:

3.160 inches

Second Leg Width:

2.000 inches

First Leg Hole Diameter:

Between 0.749 inches and 0.751 inches

Second Leg Hole Diameter:

0.250 inches

Second Leg Distance Between Hole Centers Along Width:

1.375 inches

Second Leg Distance Between Hole Centers Along Length:

1.375 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.312 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.285 inches

First Leg Thickness:

0.407 inches

Second Leg Thickness:

0.428 inches

Center Section Height:

4.500 inches

Center Section Width:

2.000 inches

Center Section Thickness:

Between 0.460 inches and 0.480 inches

First Leg Width:

2.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Length:

0.590 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

0.7485-0.7505 in. Diameter hole with 1.50-1.56 in. Diameter cbore surrounding the hole which is centrally located between the two mounting holes in the second leg; optional material: investment casting, ic-1020 or ic-1030, nomalized, mil-s-22141; apply solid film lubricant per mil-l-46010 as final surface treatment; 0.752-0.762 in.Dia hole located in center section

Material:

Steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025

Material Specification:

Astm a576 assn standard all material responses

Surface Treatment:

Cadmium and chromate and paint

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification 1st treatment response and qq-p-416, type 2, cl 3 federal specification 2nd treatment response and tt-c-490, type 3 federal specification 3rd treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0