NSN 5340-01-354-0788

Swivel Caster - Page 1 of 1

A25600



View Online at https://aerobasegroup.com/nsn/5340-01-354-0788

| view Online at https://aerobasegroup.com/nsn/3545-07-05 |
|--|
| Center To Center Distance Between Bolt Holes Along Width: |
| 7.000 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 9.750 inches |
| Wheel Quantity: |
| 1 |
| Safe Operating Load Rating: |
| 1000.0 pounds |
| Material And Location: |
| Steel body err-100 err-100 steel plate err-100 err-100 iron, cast wheel rim err-100 err-100 rubber, soft tread err-100 err-100 |
| Surface Treatment And Location: |
| Aluminum enamel bodyaluminum enamel plate |
| Wheel Type: |
| Built up |
| Wheel Diameter: |
| 10.000 inches |
| Effective Height: |
| 12.875 inches |
| Plate Style: |
| Rectangular |
| Tread Width: |
| 3.000 inches |
| Caster Plate Length: |
| 11.000 inches |
| Caster Plate Width: |
| 8.500 inches |
| Caster Plate Mounting Hole Diameter: |
| 0.625 inches |
| Style Designator: |
| Swivel offset |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filia: |