

View Online at <https://aerobasegroup.com/nsn/5340-01-354-3760>

**Mounting Hole Type:**

Plain

**First Leg Length:**

2.190 inches

**Second Leg Length:**

2.810 inches

**Second Leg Width:**

5.630 inches

**First Leg Slot Length:**

0.254 inches

**First Leg Slot Width:**

Between 0.192 inches and 0.198 inches

**Second Leg Distance Between Hole Centers Along Width:**

4.240 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.000 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.695 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.800 inches

**Second Leg Slot Length:**

0.254 inches

**Second Leg Slot Width:**

Between 0.192 inches and 0.198 inches

**First Leg Thickness:**

0.120 inches

**Second Leg Thickness:**

0.090 inches

**First Leg Width:**

5.630 inches

**First Leg Distance Between Hole Centers Along Width:**

4.375 inches

**First Leg Distance Between Hole Centers Along Length:**

0.445 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.628 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.421 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

4 slots

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

4 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Copper alloy

**Material Specification:**

Qq-c-576 federal specification single material response

**Surface Treatment:**

Tin

**Surface Treatment Specification:**

Mil-t-10727 type 1 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-t-10727 spec.