

View Online at <https://aerobasegroup.com/nsn/5340-01-354-3760>

Mounting Hole Type:

Plain

First Leg Length:

2.190 inches

Second Leg Length:

2.810 inches

Second Leg Width:

5.630 inches

First Leg Slot Length:

0.254 inches

First Leg Slot Width:

Between 0.192 inches and 0.198 inches

Second Leg Distance Between Hole Centers Along Width:

4.240 inches

Second Leg Distance Between Hole Centers Along Length:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.695 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.800 inches

Second Leg Slot Length:

0.254 inches

Second Leg Slot Width:

Between 0.192 inches and 0.198 inches

First Leg Thickness:

0.120 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

5.630 inches

First Leg Distance Between Hole Centers Along Width:

4.375 inches

First Leg Distance Between Hole Centers Along Length:

0.445 inches

First Leg Distance From Edge To Hole Center Along Width:

0.628 inches

First Leg Distance From Edge To Hole Center Along Length:

0.421 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

4 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

4 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Copper alloy

Material Specification:

Qq-c-576 federal specification single material response

Surface Treatment:

Tin

Surface Treatment Specification:

Mil-t-10727 type 1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-t-10727 spec.