

View Online at <https://aerobasegroup.com/nsn/5340-01-354-6663>

Mounting Hole Type:

Plain and threaded

First Leg Length:

0.875 inches

Second Leg Length:

1.250 inches

Second Leg Width:

2.000 inches

First Leg Hole Diameter:

0.133 mils and 0.139 centimeters

Second Leg Hole Diameter:

0.086 inches

Second Leg Distance Between Hole Centers Along Width:

1.650 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.175 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.150 inches

First Leg Thickness:

0.120 inches

First Leg Width:

2.000 inches

First Leg Distance Between Lower Hole Centers Along Width:

1.650 inches

First Leg Distance Between Hole Centers Along Length:

0.400 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.825 inches

First Leg Distance From Edge To Hole Center Along Width:

0.175 inches

First Leg Distance From Edge To Hole Center Along Length:

0.175 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Color black, no. 37038 per fed. Standard 595

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-225/8 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, cl 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.