# NSN 5340-01-355-0960

Spacing Threaded Standoff - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-355-0960

Th	rea	d (	CI	ass:

2b left internal (includes through thread)

### **Thread Direction:**

Right-hand left internal (includes through thread)

# Thread Length:

0.188 inches left internal (includes through thread)

### **Hole Diameter:**

Between 0.148 inches and 0.153 inches

### Length:

Between 0.495 inches and 0.505 inches

### **Cross-sectional Length:**

Between 0.495 inches and 0.505 inches

#### **Cross-sectional Width:**

Between 0.100 inches and 0.110 inches

### **Cross-sectional Shape:**

Rectangular

# Thready Qty Per Inch (tpi):

32 left internal (includes through thread)

### **Thread Size:**

0.250 inches left internal (includes through thread)

# **Right Projection Diameter:**

Between 0.177 inches and 0.188 inches

# Right Projection Length:

Between 0.100 inches and 0.105 inches

### Material:

Stainless steel

# **Material Specification:**

Astm a582 assn standard single material response

### **Surface Treatment:**

**Passivate** 

# **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

# **Thread Series Designator:**

Unc left internal (includes through thread)

### Shelf Life:

N/a

### **Unit Of Measure:**

--

# Demilitarization:

No

### Fiig:

A08900