

View Online at <https://aerobasegroup.com/nsn/5340-01-355-4873>

Mounting Hole Type:

Plain

First Leg Length:

Between 5.880 inches and 6.120 inches

Second Leg Length:

Between 13.880 inches and 14.120 inches

Reinforcement Method (non-core):

Gusset both legs

End Application:

2350-01-305-0028

Second Leg Width:

Between 7.940 inches and 8.060 inches

Second Leg End Width:

5.000 inches

First Leg Hole Diameter:

Between 0.530 inches and 0.590 inches

Second Leg Hole Diameter:

Between 0.405 inches and 0.465 inches

Second Leg Distance Between Hole Centers Along Width:

7.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.625 inches

First Leg Thickness:

0.500 inches

Second Leg Thickness:

0.500 inches

First Leg Width:

Between 7.380 inches and 7.620 inches

First Leg End Width:

Between 1.380 inches and 1.620 inches

First Leg Distance Between Upper Hole Centers Along Width:

6.000 inches

First Leg Distance Between Hole Centers Along Length:

Between 5.880 inches and 6.120 inches

First Leg Distance Between First And Second Hole Centers Along Width:

3.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Square and tapered

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 5052 or aluminum alloy 5083 or aluminum alloy 6061

Material Specification:

Qq-a-250/8, h32, h34 federal specification 1st material response or qq-a-250/6, h321 federal specification 2nd material response or qq-a-250/11, t651 federal specification 3rd material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0