

View Online at <https://aerobasegroup.com/nsn/5340-01-356-5117>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.380 inches

**Second Leg Length:**

0.380 inches

**First Leg Hole Diameter:**

Between 0.155 inches and 0.157 inches

**First Leg Thickness:**

Between 0.037 inches and 0.043 inches

**Second Leg Thickness:**

Between 0.037 inches and 0.043 inches

**Center Section Height:**

1.500 inches

**Center Section Width:**

2.230 inches

**Center Section Thickness:**

Between 0.037 inches and 0.043 inches

**First Leg Width:**

1.500 inches

**First Leg Distance Between Hole Centers Along Width:**

0.875 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.427 inches and 0.447 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.115 inches and 0.135 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Special Features:**

Nfurn w/three add'l. Holes in brackets' center section, one plain through hole 0.157 in. Dia. And two counterbored through holes 0.134 in. Min 0.138 in. Maximum through diameter with 0.160 in. Min 0.165 in. Maximum counterbore 82 degrees

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11, t4 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, cl 1a military specification single treatment response

**Style Designator:**

Adjacent angles

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.