

View Online at <https://aerobasegroup.com/nsn/5340-01-356-5117>

Mounting Hole Type:

Plain

First Leg Length:

0.380 inches

Second Leg Length:

0.380 inches

First Leg Hole Diameter:

Between 0.155 inches and 0.157 inches

First Leg Thickness:

Between 0.037 inches and 0.043 inches

Second Leg Thickness:

Between 0.037 inches and 0.043 inches

Center Section Height:

1.500 inches

Center Section Width:

2.230 inches

Center Section Thickness:

Between 0.037 inches and 0.043 inches

First Leg Width:

1.500 inches

First Leg Distance Between Hole Centers Along Width:

0.875 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.427 inches and 0.447 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.115 inches and 0.135 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

Nfurn w/three add'l. Holes in brackets' center section, one plain through hole 0.157 in. Dia. And two counterbored through holes 0.134 in. Min 0.138 in. Maximum through diameter with 0.160 in. Min 0.165 in. Maximum counterbore 82 degrees

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t4 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.