

View Online at <https://aerobasegroup.com/nsn/5340-01-357-1397>

**Flange Thickness:**

Between 0.260 inches and 0.280 inches

**Overall Height:**

Between 0.4945 inches and 0.4985 inches

**End Application:**

7.62mm armament subsy

**Design Type:**

Flange

**Special Features:**

Alternate materials ams 6395, 4140 or 4142; or ams 6359, 4340, hot rolled or cold finished or astm-a322 hot rolled or astm-a331 cold finished; 4130, 4140 or 4340; or 172a1659; alternate surface treatments are phosphate coating 5.3.1.3 or 5.3.2.3 of mil-std-171 w/dimensions applying before coating.; item is round in shape od 3.860 in. Porm 0.030 in., id 2.254 in porm 0.005 in.; there are 2 mtg holes, 1 has diameter 0.3795 in. Porm 0.0025 w/dist from cntr of item to 1st hole 1.486 in.; 2nd hole has diameter 0.225 in. Porm 0.007 in., w/dist from cntr of item to hole cntr 1.450 in.; 2nd hole cbored to diameter 0.440 in. Porm 0.020 in. To depth of 0.380. Porm 0.020 in.; flange radius 2.440 in. Porm 0.030 in

**Material:**

Steel

**Material Specification:**

Mil-s-18729 military specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-std-171 military standard single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A536n0

**Mil-std (military Standard):**

Mil-s-18729 spec.