

View Online at <https://aerobasegroup.com/nsn/5340-01-357-4504>

Cross Sectional Shape:

Flat

Body Thickness:

0.090 inches

Securing Device Type:

Special

End Application:

Amraam lau128a/a

Features Provided:

Special marking

Special Features:

Xitem is part of an assembly requiring 1 hinge p/n 7002806-1, hinge has 6 mtg holes and 3 knuckles; also required is 1 latch assembly p/n 654347-1, 4 rivets p/n ms20426ada w/rivet length selected iaw mil-std-403 from p/n ms20426ad4-4f-5 through ms 20426ad4-6f and 3 rivets p/n ms20470ad4 w/rivet length selected iaw mil-std-403 from p/n ms20470ad4-4f through ms20426ad4-6f; item has 2 adtl holes w/dia 0.890 to 0.901 in. Thru, c to c distance btwn holes 1.380 in.; item has corner radius of 0.190 in. 4 pl

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 t-6 federal specification single material response

Surface Treatment:

Chromate and primer and paint

Surface Treatment Specification:

Mil-c-5541, cl a military specification 1st treatment response and mil-p-23377 type optl military specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A531n0

Mil-std (military Standard):

Mil-c-5541 spec.