NSN 5340-01-358-1366

Mechanical Stop - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-358-1366

7.62mm armament subsy Design Type: Flange Special Features: Item is circular in shape w/od of 0.386 in. Porm 0.030 in., & id of 2.254 in. Porm 0.005 in.; item has 2 holes, 1 hole w/dia 0.3795 in.	ı. Porm
End Application: 7.62mm armament subsy Design Type: Flange Special Features: Item is circular in shape w/od of 0.386 in. Porm 0.030 in., & id of 2.254 in. Porm 0.005 in.; item has 2 holes, 1 hole w/dia 0.3795 in.	ı. Porm
Design Type: Flange Special Features: Item is circular in shape w/od of 0.386 in. Porm 0.030 in., & id of 2.254 in. Porm 0.005 in.; item has 2 holes, 1 hole w/dia 0.3795 in.	ı. Porm
Flange Special Features: Item is circular in shape w/od of 0.386 in. Porm 0.030 in., & id of 2.254 in. Porm 0.005 in.; item has 2 holes, 1 hole w/dia 0.3795 in.	ı. Porm
Special Features: Item is circular in shape w/od of 0.386 in. Porm 0.030 in., & id of 2.254 in. Porm 0.005 in.; item has 2 holes, 1 hole w/dia 0.3795 in.	ı. Porm
Item is circular in shape w/od of 0.386 in. Porm 0.030 in., & id of 2.254 in. Porm 0.005 in.; item has 2 holes, 1 hole w/dia 0.3795 in.	ı. Porm
·	ո. Porm
0.0025 in. & 1 hole w/dia 0.225 in. Porm 0.007 in. That is cbored 0.440 in. Porm 0.020 in. To depth of 0.380 in. Porm 0.020 in.; ite	m is heat
treated mil-h-6875, quench and temper to 33-38 rockwell 'c'; phosphate coating of 5.3.1.3 or 5.3.2. (mil-std-171) w/dimensions approximately mil-h-6875, quench and temper to 33-38 rockwell 'c'; phosphate coating of 5.3.1.3 or 5.3.2. (mil-std-171)	oplicable
prior to coating	
Material:	
Steel	
Material Specification:	
Mil-s-18729 military specification single material response	
Surface Treatment:	
Phosphate	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A536n0	
Mil-std (military Standard):	
Mil-s-18729 spec.	