Angle Bracket - Page 1 of 2





Mounting Hole Type:
Plain
First Leg Length:
4.730 inches
Second Leg Length:
4.880 inches
Reinforcement Method (non-core):
Gusset both legs
Second Leg Width:
4.340 inches
First Leg Slot Length:
2.060 inches
First Leg Slot Width:
1.560 inches
Second Leg Hole Diameter:
0.531 inches
Second Leg Distance Between Upper Hole Centers Along Width:
1.460 inches
Second Leg Distance Between Hole Centers Along Length:
2.090 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
0.730 inches
Second Leg Distance From Edge To Hole Center Along Width:
1.060 inches
Second Leg Distance From Edge To Hole Center Along Length:
1.750 inches
First Leg Thickness:
0.1793 inches
Second Leg Thickness:
0.1793 inches
First Leg Width:
4.340 inches
First Leg Distance From Edge To Hole Center Along Width:
2.150 inches
First Leg Distance From Edge To Hole Center Along Length:
1.940 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
One slot
Second Leg Style:
Square

NSN 5340-01-358-5588

Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Includes one bar p/n 12342511, welded to both gussets

Material:

Steel

Material Specification:

Astm a607 assn standard single material response or astm a606 assn standard single material response or sae j1392 assn standard single

material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0