

View Online at <https://aerobasegroup.com/nsn/5340-01-359-3661>

Mounting Hole Type:

Plain

First Leg Length:

1.040 inches

Second Leg Length:

1.340 inches

Reinforcement Method (non-core):

Turned edge second leg

Second Leg Width:

0.500 inches

Second Leg End Width:

0.380 inches

First Leg Hole Diameter:

Between 0.217 inches and 0.219 inches

Second Leg Hole Diameter:

Between 0.217 inches and 0.219 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.240 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.320 inches

First Leg Thickness:

Between 0.046 inches and 0.054 inches

Second Leg Thickness:

Between 0.046 inches and 0.054 inches

Center Section Height:

4.080 inches

Center Section Width:

1.200 inches

Center Section Thickness:

Between 0.046 inches and 0.054 inches

First Leg Width:

1.140 inches

First Leg End Width:

1.020 inches

First Leg Distance Between Lower Hole Centers Along Width:

0.660 inches

First Leg Distance Between Hole Centers Along Length:

0.420 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.330 inches

First Leg Distance From Edge To Hole Center Along Width:

0.240 inches

First Leg Distance From Edge To Hole Center Along Length:

0.230 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

Between 40.0 degrees and 50.0 degrees

Second Leg Chamfer Angle:

Between 40.0 degrees and 50.0 degrees

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 h32 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 cl 3 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.