

View Online at <https://aerobasegroup.com/nsn/5340-01-360-5239>

**Center To Center Distance Between Bolt Holes Along Width:**

2.625 inches

**Center To Center Distance Between Bolt Holes Along Length:**

3.625 inches

**Wheel Quantity:**

1

**Safe Operating Load Rating:**

640.0 pounds

**Material And Location:**

Plastic, phenolic resin, cotton fabric base tread err-100 err-100 plastic, phenolic laminate, cloth base wheel rim err-100 err-100 steel body err-100 err-100 or iron, cast body err-100 err-100 or aluminum alloy body err-100 err-100 steel plate err-100 err-100

**Surface Treatment And Location:**

Cadmium plate or zinc plated plate or painted plate or lacquer plate or enamel plate

**Wheel Type:**

Built up

**Wheel Diameter:**

6.000 inches

**Effective Height:**

7.375 inches

**Features Provided:**

Swivel lubrication fitting

**Plate Style:**

Rectangular

**Wheel Bearing Type:**

Roller or ball

**Swivel Bearing Type:**

Annular ball

**Swivel Bearing Arrangement:**

Two row or two level

**Tread Width:**

2.000 inches

**Caster Plate Length:**

5.500 inches

**Caster Plate Width:**

5.000 inches

**Caster Plate Mounting Hole Diameter:**

0.375 inches

**Special Features:**

No surface finish on aluminum casters; optional mounting plate hole spacing 3.000 in. By 3.000 in.; optional height 8.000 in.

**Style Designator:**

Swivel offset

**Specification Or Standard:**

A group and 2 type and 4 class and 1 style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A25600