

View Online at <https://aerobasegroup.com/nsn/5340-01-362-2119>

Mounting Hole Type:

Threaded

First Leg Length:

1.500 inches

Second Leg Length:

3.560 inches

Second Leg Width:

3.310 inches

First Leg Hole Diameter:

Between 0.213 inches and 0.216 inches

Second Leg Hole Diameter:

Between 0.1875 inches and 0.1878 inches

Second Leg Distance Between Hole Centers Along Width:

2.812 inches

Second Leg Distance Between Hole Centers Along Length:

2.812 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

3.310 inches

First Leg Distance Between Upper Hole Centers Along Width:

2.812 inches

First Leg Distance Between Hole Centers Along Length:

0.750 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.406 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

One aperture located on second leg, 3.000 in. Dia

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 t4 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.