

View Online at <https://aerobasegroup.com/nsn/5340-01-362-3443>

Mounting Hole Type:

Plain

First Leg Length:

0.700 inches

Second Leg Length:

6.200 inches

Second Leg Width:

5.250 inches

First Leg Hole Diameter:

Between 0.155 inches and 0.161 inches

Second Leg Hole Diameter:

Between 0.158 inches and 0.164 inches

Second Leg Distance Between Hole Centers Along Width:

4.872 inches

Second Leg Distance Between Hole Centers Along Length:

5.125 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.189 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

5.250 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.500 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

1.500 inches

First Leg Distance From Edge To Hole Center Along Width:

1.380 inches

First Leg Distance From Edge To Hole Center Along Length:

0.280 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

One aperture on second leg, 4.000 in. Sq.

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 h32 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.