

View Online at <https://aerobasegroup.com/nsn/5340-01-364-4347>

**Mounting Hole Type:**

Countersunk and plain

**First Leg Length:**

1.280 inches

**Second Leg Length:**

2.450 inches

**Second Leg Width:**

2.040 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

0.344 inches

**Second Leg Distance Between Second And Third Hole Centers Along Width:**

0.344 inches

**First Leg Thickness:**

Between 0.115 inches and 0.135 inches

**Second Leg Thickness:**

Between 0.115 inches and 0.135 inches

**Center Section Height:**

1.475 inches

**Center Section Width:**

2.040 inches

**Center Section Thickness:**

Between 0.115 inches and 0.135 inches

**First Leg Width:**

2.040 inches

**First Leg End Width:**

1.200 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

0.500 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

0.500 inches

**Second Leg End Radius:**

1.020 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

Three holes

**Features Provided:**

Nut

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-225/6 t351 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541 cl1a military specification single treatment response

**Style Designator:**

Adjacent angles

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.