
NSN 5340-01-365-3257

Double Angle Bracket - Page 1 of 2





Mounting Hole Type:
Plain
First Leg Length:
0.560 inches
Second Leg Length:
0.585 inches
First Leg Hole Diameter:
0.1969 inches
Second Leg Hole Diameter:
Between 0.4062 inches and 0.4072 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.300 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.300 inches
First Leg Thickness:
0.170 inches
Second Leg Thickness:
0.230 inches
Center Section Height:
0.410 inches
First Leg Width:
1.453 inches
First Leg Corner Radius:
0.220 inches
First Leg Distance Between Hole Centers Along Width:
1.013 inches
First Leg Distance From Edge To Hole Center Along Width:
0.220 inches
First Leg Distance From Edge To Hole Center Along Length:
0.220 inches
Second Leg End Radius:
0.300 inches
First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
End radius and tapered
Second Leg Hole Arrangement Style:
One hole
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees

NSN 5340-01-365-3257

Double Angle Bracket - Page 2 of 2



Material:

Aluminum alloy 7075

Material Specification:

Qq-a-200/11 t73 federal specification single material response

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-83286 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-83286 spec.