

View Online at <https://aerobasegroup.com/nsn/5340-01-368-4710>

Mounting Hole Type:

Plain

First Leg Length:

1.380 inches

Second Leg Length:

1.750 inches

Second Leg Width:

30.690 inches

First Leg Slot Length:

2.500 inches

First Leg Slot Width:

0.560 inches

Second Leg Distance Between Hole Centers Along Width:

28.875 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.849 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.442 inches

Second Leg Slot Length:

0.938 inches

Second Leg Slot Width:

0.438 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

30.690 inches

First Leg End Width:

28.440 inches

First Leg Distance Between Hole Centers Along Width:

23.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.445 inches

First Leg Style:

Angle

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6061 or aluminum alloy 6063

Material Specification:

Qq-a-200/8 t6 federal specification single material response or qq-a-200/9 t52 federal specification single material response

Surface Treatment:

Paint

Surface Treatment Specification:

Mil-c-22750 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-22750 spec.