

View Online at <https://aerobasegroup.com/nsn/5340-01-368-4710>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.380 inches

**Second Leg Length:**

1.750 inches

**Second Leg Width:**

30.690 inches

**First Leg Slot Length:**

2.500 inches

**First Leg Slot Width:**

0.560 inches

**Second Leg Distance Between Hole Centers Along Width:**

28.875 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.849 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.442 inches

**Second Leg Slot Length:**

0.938 inches

**Second Leg Slot Width:**

0.438 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

30.690 inches

**First Leg End Width:**

28.440 inches

**First Leg Distance Between Hole Centers Along Width:**

23.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.750 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.445 inches

**First Leg Style:**

Angle

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 6061 or aluminum alloy 6063

**Material Specification:**

Qq-a-200/8 t6 federal specification single material response or qq-a-200/9 t52 federal specification single material response

**Surface Treatment:**

Paint

**Surface Treatment Specification:**

Mil-c-22750 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-22750 spec.