## NSN 5340-01-368-5659

Double Angle Bracket - Page 1 of 2

Mounting Hole Type:
Plain and threaded
First Leg Length:



View Online at https://aerobasegroup.com/nsn/5340-01-368-5659

2.250 inches
Second Leg Width:
30.000 inches
Second Leg Hole Diameter:
0.500 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
12.500 inches
Second Leg Distance Between Second And Third Hole Centers Along Width:
12.500 inches
Second Leg Distance From Edge To Hole Center Along Width:
2.500 inches
First Leg Thickness:
0.810 inches
Second Leg Thickness:
1.310 inches
Center Section Height:
3.680 inches
Center Section Width:
30.000 inches
First Leg Width:
30.000 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
3 slots
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
Three holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Material:
Aluminum alloy 5083 or aluminum alloy 2014
Material Specification:
Mil-a-46083 cl 1 military specification 1st material response or mil-a-46027 military specification 1st material response or qq-a-200/2 t6
federal specification 2nd material response

## NSN 5340-01-368-5659

Double Angle Bracket - Page 2 of 2

Mil-std (military Standard):

Mil-a-46083 spec.



Surface Treatment:
Plastic polyurethane
Surface Treatment Specification:
$lem:military specification single treatment response or mil-c-53039\ military\ specification\ single\ treatment\ response$
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A042a0