

View Online at <https://aerobasegroup.com/nsn/5340-01-369-1376>

Mounting Hole Type:

Plain

First Leg Length:

Between 72.0 millimeters and 74.0 millimeters

Second Leg Length:

Between 72.0 millimeters and 74.0 millimeters

End Application:

Mrap - common nsn - used on 3 mrap variants and 1 other weapon system

First Leg Thickness:

8.0 major inches

Second Leg Thickness:

8.0 major inches

Center Section Height:

70.0 millimeters

Center Section Width:

Between 79.0 millimeters and 81.0 millimeters

Center Section Thickness:

8.0 millimeters

First Leg Width:

Between 79.0 millimeters and 81.0 millimeters

First Leg End Width:

Between 19.0 millimeters and 21.0 millimeters

First Leg Distance Between Upper Hole Centers Along Width:

52.0 millimeters

First Leg Distance Between Hole Centers Along Length:

25.0 millimeters

First Leg Distance Between First And Second Hole Centers Along Width:

26.0 millimeters

First Leg Distance From Edge To Hole Center Along Width:

14.0 major inches

First Leg Distance From Edge To Hole Center Along Length:

25.0 major inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel

Material Specification:

Astm a36 gr 36 assn standard single material response

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.