

View Online at <https://aerobasegroup.com/nsn/5340-01-369-1376>

**Mounting Hole Type:**

Plain

**First Leg Length:**

Between 72.0 millimeters and 74.0 millimeters

**Second Leg Length:**

Between 72.0 millimeters and 74.0 millimeters

**End Application:**

Mrap - common nsn - used on 3 mrap variants and 1 other weapon system

**First Leg Thickness:**

8.0 major inches

**Second Leg Thickness:**

8.0 major inches

**Center Section Height:**

70.0 millimeters

**Center Section Width:**

Between 79.0 millimeters and 81.0 millimeters

**Center Section Thickness:**

8.0 millimeters

**First Leg Width:**

Between 79.0 millimeters and 81.0 millimeters

**First Leg End Width:**

Between 19.0 millimeters and 21.0 millimeters

**First Leg Distance Between Upper Hole Centers Along Width:**

52.0 millimeters

**First Leg Distance Between Hole Centers Along Length:**

25.0 millimeters

**First Leg Distance Between First And Second Hole Centers Along Width:**

26.0 millimeters

**First Leg Distance From Edge To Hole Center Along Width:**

14.0 major inches

**First Leg Distance From Edge To Hole Center Along Length:**

25.0 major inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Material:**

Steel

**Material Specification:**

Astm a36 gr 36 assn standard single material response

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

**Style Designator:**

Adjacent angles

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.