

View Online at <https://aerobasegroup.com/nsn/5340-01-369-6113>

First Leg Length:

Between 0.615 inches and 0.655 inches

Second Leg Length:

0.312 inches

Second Leg Width:

2.950 inches

First Leg Slot Width:

Between 0.220 inches and 0.258 inches

Second Leg Distance Between Hole Centers Along Width:

2.375 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.290 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.500 inches

Second Leg Slot Length:

2.500 inches

Second Leg Slot Width:

Between 0.220 inches and 0.250 inches

First Leg Thickness:

0.065 inches

Second Leg Thickness:

0.065 inches

First Leg Width:

2.630 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.625 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.438 inches

First Leg Distance Between Third And Fourth Hole Centers Along Width:

0.625 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

4 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

1st leg slots through end

Material:

Steel

Material Specification:

Astm a366 assn standard single material response or astm a109 assn standard single material response

Surface Treatment:

Paint

Surface Treatment Specification:

Mil-c-22750, light green no. 24533 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-22750 spec.