# NSN 5340-01-369-6137

Spacing Threaded Standoff - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-369-6137

#### **Thread Class:**

2b left internal (includes through thread)2a right external

#### **Thread Direction:**

Right-hand left internal (includes through thread)right-hand right external

#### Thread Length:

0.500 inches left internal (includes through thread)0.371 inches and 0.379 inches right external

#### Length:

Between 0.995 inches and 1.005 inches

#### **Cross-sectional Shape:**

Hexagon

#### Width Across Flats:

Between 0.369 inches and 0.381 inches

#### Thready Qty Per Inch (tpi):

32 left internal (includes through thread)32 right external

#### Thread Size

0.190 inches left internal (includes through thread)0.190 inches right external

## **Right Projection Diameter:**

0.190 inches

# **Right Projection Length:**

Between 0.371 inches and 0.379 inches

#### Material:

Aluminum alloy 2011 or aluminum alloy 2024 or aluminum alloy 6061

#### **Material Specification:**

Qq-a-225/3 t4 federal specification 1st material response or qq-a-225/6 t4 federal specification 2nd material response or qq-a-225/8 t6 federal specification 3rd material response

# **Surface Treatment:**

Anodize

#### **Surface Treatment Specification:**

Mil-a-8625, type 1 or 2, cl 1 military specification single treatment response

#### **Style Designator:**

Left internal and right external thread

# **Thread Series Designator:**

Unf left internal (includes through thread)unf right external

#### **Specification Data:**

80205-nas1829 professional/industrial association standard

#### Shelf Life:

N/a

# **Unit Of Measure:**

## Demilitarization:

No

# Fiig:

A08900

# NSN 5340-01-369-6137

Spacing Threaded Standoff - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.