NSN 5340-01-370-2347

Spacing Threaded Standoff - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-370-2347

		_		
TL	rea	_	\sim	

2b left internal (includes through thread)2a right external

Thread Direction:

Right-hand left internal (includes through thread)right-hand right external

Thread Length:

0.470 inches and 0.530 inches left internal (includes through thread)0.470 inches and 0.530 inches right external

Length:

Between 1.240 inches and 1.260 inches

Cross-sectional Shape:

Hexagon

Width Across Flats:

Between 0.365 inches and 0.385 inches

Thready Qty Per Inch (tpi):

32 left internal (includes through thread)32 right external

0.138 inches left internal (includes through thread)0.138 inches right external

Right Projection Diameter:

0.138 inches

Right Projection Length:

Between 0.470 inches and 0.530 inches

Material:

Stainless steel

Material Specification:

Astm a581 assn standard single material response or astm a582 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Left internal and right external thread

Thread Series Designator:

Unc left internal (includes through thread)unc right external

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A08900